PHGenFit: Path length extraction

Previous interface:

```
genfit::MeasuredStateOnPlane* Track::extrapolateToXXX(..., const int tr point id = 0)
```

Added a new interface that returns the path length, old interface also still available.

```
double Track::extrapolateToXXX(genfit::MeasuredStateOnPlane& state, ..., const int tr_point_id = 0)
The path length is calculated w.r.t. the given measurement (default 0).
```

Merged into J. Lajoie's repository, would come to the sPHENIX repository with P.R. #201

https://github.com/johnlajoie/coresoftware/pull/6







Investigate momentum/dca reconstruction Ladder MAPS + TPC

Jin Huang(BNL), Anthony Frawley(FSU), Haiwang Yu (NMSU)

Problems

- pT offset is off 0
- \diamond dca2d pull σ (σ (dca2d/error)) is off 1.
- Possible origins:
 - field map inconsistency
 - clustering (center values, uncertainties)
- I checked the field map settings, and it seems I used consistent field maps:
 - /phenix/upgrades/decadal/fieldmaps/sPHENIX.2d.root
 - Scaled by 1.4/1.5
- We have a FastSim (truth tracking) module "PHG4TrackFastSim" which can do Kalman Fitting based on smeared PHG4Hits.
 - The central value is the PHG4Hit average position of the in and out hits
 - The smearing is given according to detector resolution
 - So there is no clustering involved






Alan (no PHG4SvtxMomentumRecal, grey) vs. FastSim/Truth Tracking (Black)

FastSim Setup:

- Takes both MAPS and TPC PHG4Hits
- Assign 100 micron resolution to both phi and z resolution
 - All the absolute resolutions don't reflect true detector performance
 - Offsets and pull distributions still make sense
- The reconstructed pT offset is 0.
- The dca2d pull σ is close to 1.



Alan (no PHG4SvtxMomentumRecal, grey) vs. GenFit (with correct norm vectors, Black)

- GenFit refitted results:
 - Better pT resolution at high pT
 - Better dca2d resolution at low pT
 - Dca2d offsets are closer to 0

